

STRADELLA-IP-28-HB-M

~65° medium beam. Variant made from PMMA.



TECHNICAL SPECIFICATIONS:

Dimensions	100.0 mm
Height	9.5 mm
Fastening	pin, screw
Colour	clear
Box size	476 x 273 x 247 mm
Box weight	5.8 kg
Quantity in Box	156 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:



Component	Type	Material	Colour
STRADELLA-IP-28-HB-M	Lens array	PMMA	clear
STRADELLA-28-SEAL	Seal	Silicone	white



PHOTOMETRIC DATA (MEASURED):

CREE 


LED XT-E
FWHM 70.0°
Efficiency 94 %
Peak intensity 0.600 cd/lm
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XP-G3
FWHM 76.0°
Efficiency 94 %
Peak intensity 0.550 cd/lm
Required components:




LED LUXEON 3030 2D (Round LES)
FWHM 58.0°
Efficiency 92 %
Peak intensity 0.760 cd/lm
Required components:



LED LUXEON 5050
FWHM 69.0°
Efficiency 94 %
Peak intensity 0.650 cd/lm
Required components:




LED NF2x757G
FWHM 63.0°
Efficiency 94 %
Peak intensity 0.710 cd/lm
Required components:




PHOTOMETRIC DATA (SIMULATED):



LED NF2x757G
FWHM 63.0°
Efficiency 94 %
Peak intensity 0.710 cd/lm
Required components:




LED NVSxE21A
FWHM 58.0°
Efficiency 92 %
Peak intensity 0.736 cd/lm
Required components:




Opto Semiconductors

LED Duris S5 (2 chip)
FWHM 64.0°
Efficiency 94 %
Peak intensity 0.960 cd/lm
Required components:



Opto Semiconductors


LED Duris S8
FWHM 67.0°
Efficiency 94 %
Peak intensity 0.690 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):


OSRAM
Opto Semiconductors

LED Oslon Square Gen3
FWHM 68.0°
Efficiency 93 %
Peak intensity 0.610 cd/lm
Required components:




SAMSUNG

LED LH181B
FWHM 65.0°
Efficiency 94 %
Peak intensity 0.680 cd/lm
Required components:




SAMSUNG

LED LH351B
FWHM 71.0°
Efficiency 94 %
Peak intensity 0.720 cd/lm
Required components:



SAMSUNG


LED LH351C
FWHM 75.0°
Efficiency 94 %
Peak intensity 0.683 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED LM301B
FWHM 63.0°
Efficiency 94 %
Peak intensity 0.700 cd/lm
Required components:




SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2
FWHM 70.0°
Efficiency 94 %
Peak intensity 0.640 cd/lm
Required components:




SEOUL SEMICONDUCTOR

LED Z8Y19
FWHM 65.0°
Efficiency 94 %
Peak intensity 0.680 cd/lm
Required components:



SEOUL SEMICONDUCTOR

LED Z8Y22
FWHM 76.0°
Efficiency 92 %
Peak intensity 0.586 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)