

### **HB-SQ-WWW**

~90° beam. Assembly with installation tape.

### **TECHNICAL SPECIFICATIONS:**

Dimensions 25x 25 mm

Height 10 mm

Fastening tape, pin

Colour clear

Box size 480 x 280 x 300 mm

Box weight 8.9 kg

Quantity in Box 2058 pcs


ROHS compliant yes 10



### **MATERIAL SPECIFICATIONS:**

Component	Type	Material	Colour
HB-SQ-WWW	Lens	PMMA	clear
ROSE-TAPE	Tape	PU tape	black





### PHOTOMETRIC DATA (SIMULATED):

bridgelux.


LED SMD 5050

FWHM 77.0°

Efficiency 93 %

Peak intensity 0.540 cd/lm

Required components:



CREE 🚓


LED MHD-E/G

FWHM 85.5°

Efficiency 91 %

Peak intensity 0.450 cd/lm

Required components:



CREE 💠


LED XHP70

FWHM 83.0°

Efficiency 89 %

Peak intensity 0.500 cd/lm

Required components:



CREE 💠


LED XHP70.2

FWHM 85.0°

Efficiency 86 %

Peak intensity 0.440 cd/lm

Required components:






### PHOTOMETRIC DATA (SIMULATED):

LU	MI	LE	DS
	4		

LED LUXEON M/MX

FWHM 80.0°
Efficiency 90 %
Peak intensity 0.550 cd/lm

Required components:




#### OSRAM Opto Semiconductors

LED OSCONIQ P 7070

FWHM 75.0° Efficiency 91 % Peak intensity 0.630 cd/lm

Required components:





### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

### **Shipping locations**

Salo, Finland Hong Kong, China

### **Distribution Partners**

www.ledil.com/ where\_to\_buy